



NIMBLE-S CEILING SURFACE MOUNTED 715A



Nimble .s 尼博

715A 吸顶灯/线型灯带

Ceiling surface mounted luminaires/
continuous lighting system technical data sheet

715A 尼博线形吸顶灯为简约式LED灯具，采用优质铝合金型材灯体，无螺丝压铸铝端盖，灯具线条硬朗美观、外观尺寸比例科学，结构合理，安装维护方便灵活。PC控光面罩根据LED光波长开发，防眩光效果好，出光均匀无阴影、控光面罩与灯体完美结合使整个灯具更加美观。先进的热管理技术，散热优异，确保了灯具最大光输出的持续性及色温的一致性。此系列可做无边嵌入式安装。

应用场所：写字楼、学校、医院、高档超市、商场、酒店等公共建筑。

715A series ceiling surface mounted linear LED luminaire, housing made of high pressure extruded aluminum construction, die-cast aluminum end caps with no visible screws, UV and corrosion resistance, with beautiful appearance, the scientific proportion and reasonable dimensions, flexible installing methods, light body, excellent heat dissipation. High transmittance PC diffuser specially designed for LED light source creating smooth and uniform lighting distributions high visual comfort for all lighting applications, without visible dark spot or light gaps in seamless continuous lighting system. Advanced thermal management technology to ensure consistency of LED life span, color temperature and maximize output lumens. Trimless recessed mounted is also available for this series.

Applications: Office, Educational Institutes, Hospitals, Warehouses, Hospitality, Retail Etc.

产品细节 Details






规格参数 Technical Data

名称: 715A 吸顶灯
类型: 吸顶灯
灯体材料: 优质铝合金
表面处理: 静电喷涂
控光面罩: PC
光源: SMD
整灯光效: 80 lm/W
显色指数: ≥83
色温: 3000K / 4000K / 6500K
输入电压: 220-240V
驱动电源: 高转换率驱动电源
灯具寿命: 3万小时
电气等级: I

Product name: 715A Ceiling surface mounted luminaires
Type: Ceiling surface mounted luminaires
Housing material: High-quality Aluminum alloy
Surface finish: Electrostatic thermo-painting
Diffuser material: PC
Light source: SMD
Luminaire efficiency: 80 lm/W
CRI: ≥83
Color temperature: 3000K / 4000K / 6500K
Input voltage: 220-240V
Driver: High efficiency driver
Lifespan: 30000h
Electrical grade: I

Indoor 室内适用	General lighting 基础照明	High efficiency 高光效	Long life 长寿命	Anti glare 防眩光	Accurate light distribution 准配光
No flickering 无频闪	IP 20 Protection level 防护等级	Protective grounding 保护接地	Fire protection 防火	Low lumen depreciation 低光衰	color-temp changing 调色温驱动电源
Microwave sensor 微波感应控制	Emergency kits 应急照明组件	DALI	light control 光控	Wifi or Ble, Zigbee	1-10V 1-10V dimming 1-10V调光
China Compulsory Certification 3C认证	CE certification CE认证	CB certification CB认证			


标准灯具 Standard single fitting



低功率 (HE)

CCT: 3000K
Colors: Silver /
White / Black


Item No	Power Flux	L*W*H
715A-CS1150T18W	18W / 1440 lm	1150*43*64
715A-CS1710T27W	27W / 2160 lm	1710*43*64
715A-CS2270T36W	36W / 2880 lm	2270*43*64



低功率 (HE)

CCT4000K
Colors: Silver /
White / Black

Item No	Power Flux	L*W*H
715A-CS1150T18W	18W / 1460 lm	1150*43*64
715A-CS1710T27W	27W / 2180 lm	1710*43*64
715A-CS2270T36W	36W / 2900 lm	2270*43*64



低功率 (HE)


CCT: 6500K
Colors: Silver /
White / Black

Item No	Power Flux	L*W*H
715A-CS1150T18W	18W / 1480 lm	1150*43*64
715A-CS1710T27W	27W / 2200 lm	1710*43*64
715A-CS2270T36W	36W / 2920 lm	2270*43*64





应用参考 Application reference

Open space: 10m x 10m x 3m; reflectance (%): ceiling80/wall50/floor20/ floor ceiling walls; illuminance is the average lux level on 0.75m working surface; "H" is the fittings installation height

开放式空间: 10m x 10m x 3m; 反射率(%): 天花板 80/墙壁50/地板20; 照度为 0.75m工作面平均照度; H为灯具安装离地高度。




Item No	Power Flux	Number	W/m ²	H=2.8m Illuminance(Lux)
715A-CS1150T18W	18W / 1440 lm	36	6.48	326
715A-CS9600T144W	144W / 15120 lm	4	4.32	346



小功率 (HO-L)

CCT: 3000K
Colors: Silver /
White / Black


Item No	Power Flux	L*W*H
715A-CS1150T36W	36W / 2880 lm	1150*43*64
715A-CS1710T54W	54W / 4320 lm	1710*43*64
715A-CS2270T72W	72W / 5760 lm	2270*43*64



小功率 (HO-L)

CCT: 4000K
Colors: Silver /
White / Black

Item No	Power Flux	L*W*H
715A-CS1150T36W	36W / 2900 lm	1150*43*64
715A-CS1710T54W	54W / 4340 lm	1710*43*64
715A-CS2270T72W	72W / 5780 lm	2270*43*64



小功率 (HO-L)

CCT: 6500K
Colors: Silver /
White / Black

Item No	Power Flux	L*W*H
715A-CS1150T36W	36W / 2920 lm	1150*43*64
715A-CS1710T54W	54W / 4360 lm	1710*43*64
715A-CS2270T72W	72W / 5800 lm	2270*43*64

配件 Accessories



715A 快速光带连接件
715A Quick
continuous connector
Colors: Silver



安装卡扣
Installation buckle
Colors: Silver

线形光带示意图 Linear continuous connection demonstration

